



PERFORM. LIKE NO OTHER.™

## **Velocity™ Pumper Stock Truck # 23231**

### **Chassis:**

- Velocity chassis, 70" cab
- Overall Height: 9' 4.5"
- Overall Length: 31' 7.25"
- 6-person cab seating capacity
- Wheelbase: 191.50"
- GVW Rating: 46,800 lbs.
- Frame Rails: 13.38"
- Front Axle: TAK-4® independent front suspension, 22,800 lbs.
- Rear Axle: Meritor RS24-160, 24,000 lbs.
- Brakes: Wabco ABS/ESC/ATC system
  - Knorr/Bendix 17", disc front
  - Meritor, cam rear
- Engine: Cummins ISM, 500 hp, 1550 torque
- Transmission: Allison EVS 4000
- Lift and tow package
- Frontal occupant protection air bags
- Side roll protection system
- Command Zone™ advanced electronics system
- Air conditioning/heater/defroster
- Alternator: 340 amp Niehoff
- Front access service tilt hood

### **Pumper Body:**

- Tank: 750 gallon, polypropylene with 4" overflow
- Aluminum body
  - Gortite roll-up doors
  - Adjustable shelves, 215 lb. capacity
- (4) Storage compartments for air bottles
- Pump: Waterous 1500 gpm, single stage
- Pump Panel: Control Zone
- Plumbing: Stainless steel
- Ergonomic crosslay height
- Valves: Akron 8000 Series
- Foam System: Husky™ 12 foam system with 25 gallon foam tank

