

PERFORM. LIKE NO OTHER.

## Dash<sup>®</sup> CF PUC<sup>™</sup> Pumper Stock Truck # 23776

## **Dash CF Fosters Situational Readiness:**

- Greater Space
  - o Increased Driver & Officer Room / More Shoulder & Elbow Room / Added Storage Space
- Greater Visibility
  - Larger, Single Piece Windshield / Enhanced Internal Visibility & Communications
- Improved / Safer Steps
  - Wider Steps / Stair stepped/ Lower to Ground / Two Step Entry
- Greater Serviceability
  - Common Filter Location / Accessory Drive Access / Checks & Fills Access / Power Distribution Access / Steering Gear, Radiator, Pump, & Water Valve Access
- Heavy Duty Construction & Packaging
  - o 13" Frame Rails / Metal Interior / Lower Sound Levels / Cab Construction / PUC Platform

## Chassis:

- Dash CF chassis\*, 70" cab w/11" raised roof
- Overall Height: 9' 9"
- Overall Length: 31' 6"
- 6-person cab seating capacity
- Wheelbase: 181.00"
- GVW Rating: 46,500 lbs.
- Frame Rails: 13.38"
- Front Axle: TAK-4<sup>®</sup> independent front suspension, 19,500 lbs.
- Rear Axle: Meritor RS24-160, 24,000 lbs.
- Brakes: Wabco ABS/ESC/ATC system
  - o Knorr/Bendix 17", disc front
  - o Meritor, cam rear
- Engine: Cummins ISL9, 450 hp, 1250 ft-lb torque
- Transmission: Allison EVS 3000
- Cooling System: Auxiliary
- Command Zone<sup>™</sup> advanced electronics system
- Single Point Service Access (Common Filter Location)

## **PUC Pumper Body:**

- 177" Aluminum body (Full Height/Full Depth)
  - Gortite roll-up doors
  - Adjustable shelves, 500 lb. capacity
- Tank: 500 gallon, polypropylene with 4" overflow
- (3) Double storage compartments for air bottles
- Pump: PUC 1500 gpm, single stage
- Pump Panel: Control Zone
- · Pump and roll with two-step shift technology
- Plumbing: Stainless steel
- · Ergonomic crosslay height
- Valves: Akron 8000 Series
- Foam System: Husky<sup>™</sup> 3 foam system with 20 gallon foam tank

<sup>\*</sup>Patent Pending





