

PERFORM. LIKE NO OTHER.

Arrow XT[™] PUC[™] Stock Truck # 24886

PUC Industry Changers:

- Easier to use
- Easier to stay safe
- · Easier to store more equipment
- Easier to service
- Easier to maneuver

PUC Pumper Body:

- Tank: 500 gallon, polypropylene with 4" overflow
- Aluminum body
 - o Gortite roll-up doors
 - o Adjustable shelves, 500 lb. capacity
- (3) Storage compartments for air bottles
- Pump: Pierce PUC 1500 gpm, single stage
- Pump Panel: Control Zone
- Pump and roll with two-step shift technology
- Plumbing: Stainless steel
- · Ergonomic crosslay height
- Valves: Akron 8000 Series
- Foam System: Husky[™] 3 foam system with 30 gallon foam tank

Chassis:

- Arrow XT chassis, 67" cab with 10" raised roof
- Overall Height: 10'
- Overall Length: 29' 5.5"
- 6-person cab seating capacity
- Wheelbase: 163.50"
- GVW Rating: 42,000 lbs.
- Frame Rails: 13.38"
- Front Axle: TAK-4[®] independent front suspension, 18,000 lbs.
- Rear Axle: Meritor RS24-160, 24,000 lbs.
- Brakes: Wabco ABS/ESC/ATC system
 - o Knorr/Bendix 17", disc front
 - Meritor EX225, disc plus
- Engine: Cummins ISL9, 450 hp, 1250 torque
- Transmission: Allison EVS 3000
- Lift and tow package
- Frontal occupant protection air bags
- Side roll protection system
- Command Zone[™] advanced electronics system
- Air conditioning/heater/defroster
- Alternator: 290 amp Niehoff





