

FIRE PUMP
WATEROUR CSUY 2000 GPM MIDSHIP MOUNTED PUMP
ARR OPERATED PUMP SHIFT
ONE (1) CLASS ONE PRESSURE SENSING GOVERNOR
ONE (1) WATEROUS INTAKE RELIEF VALVE
ONE (1), WATEROUS PUMP OPERATION AND MAINTENANCE VIDEO

INLE I S
TWO (2) 6" STEAMER INLETS ONE EACH SIDE
ONE (1) 4" REAR INLET TO THE PUMP
ONE (1), 2 1/2" GATED INLET ON THE RIGHT SIDE

DISCHARGES
TWO (2) 2 1/2" NST DISCHARGES ON THE RIGHT SIDE
ONE (1) 4" NST DISCHARGE ON THE RIGHT SIDE
ONE (1) 4" DISCHARGE ON THE RIGHT SIDE
ONE (1) 4" DISCHARGE TO THE ARRAL LADDER WATERWAY
TWO (2) 1 1/2" CROSSLAY, CAPACITY FOR 200" 1 3/4" HOSE
ONE (1), 2 1/2" CROSSLAY, CAPACITY FOR 200" 07 2 1/2" HOSE
ONE (1), 2 1/2" DEBOLAY, CAPACITY FOR 200" 07 2 1/2" HOSE

WATER TANK 500 U.S. GALLON WATER TANK W/30 U.S. GALLON FOAM CELL TWO (2), CLASS I LED TANK LEVEL GAUGES ONE (1) 1 1/2" TANK JOPAN ONE (1) 3" TANK TO PUMP VALVE ONE (1) 2" TANK FILL

OPERATORS CONTROL PANEL
MATERIAL: STIANLESS STEEL
4 1/2° DIA. MASTER GAUGES
21/2° DIA. PRESSURE GAUGES
0016′ (1) CLASS 1 FLOWMETER IN THE AERIAL WATERWAY BODY CONSTRUCTION/COMPARTMENTATION MATERIAL: 3/16" 5052 ALUM. AMDOR ROLL UP DOORS AMDOR ROLL UP DOORS
FOUR (4) MUPTAPS, 2 FRONT AND 2 REAR
TWO (2) TOW EYES
ALUMINUM SCULFF PLATES IN DOOR SILLS
FOUR (4) REAR POLISHED ALUM FRIDERETTES
DRIBLES IN COMF. FLOORS
TWO (2) PARS OF WHELL CHOCKS
ONE (1) CAST PRODUCTS PUEL DOOR


HOSE BED CAPACITY: 800' OF 4" HOSE 800' OF 2 1/2" HOSE

GROUND LADDERS
ONE (1) 12* FRESNO ATTIC LADDER 701
ONE (1) 14* COMBINATION LADDER DUO SAFETY 875A
ONE (1) 14* COMBINATION LADDER DUO SAFETY 35A
ONE (1) 24* TWO SECTION EXTENSION LADDER DUO SAFETY 900A
ONE (1) 35* THREE SECTION EXTENSION LADDER DUO SAFETY 1225A

PIKE POLES
TWO (2) 6' PIKE POLES
TWO (2) 8' PIKE POLES
TWO (2) 12' PIKE POLES
TWO (2) 4' PIKE POLES
TWO (2) 4' PIKE POLES


110 VOLT ELECTRICAL SYSTEM
TWO (2), ALPHA 2000, 750 WAIT LIGHTS ON THE PLIMP COMPARTMENT
TWO (2), ALPHA 2000, 750 WAIT LIGHTS AT THE AERIAL TIP
ONE (1), 110 VOLT LOAD CENTER, LET FRONT COMPARTMENT
TWO (2), NEAM LG—15 OUT


APPARATUS COLOR: AERIAL COLOR: WHITE, PPG DITZLER DBHS-2185



AERIAL LADDER
ONE YEAR WARRANTY, PARTS AND LABOR
ONE (1) BOLT ON REMOVEABLE CORESS
ONE (1) SIST OF ROLDING SIEPS AT HAS
RETINATION SHEET STEMS
RETINATION SAFETY SISTEM SISTEM
RETINATION SAFETY SISTEMS SISTEMS
RETINATION SAFETY SISTEMS SAFETY SISTEMS
RETINATION SAFETY SISTEMS SAFETY SISTEMS
ONE (1), SISTEMSICS ROLDION/INTERCOM SISTEMS
ONE (1), SISTEMSICS ROLDION/INTERCOM SISTEMS
WATERINGY CAPACITY, DOLG ONE DESCRIPTION AND DEGREES TO THE SIDE
WATERINGY CAPACITY, DOLG ONE DEGREES TO THE SIDE

WATERWAY CAPACHY: 1000 GPM DIRECTED AT 90 DEGREES TO ONE (1) ARRON ATS 78 ELECTRE OMNOR W/NOZZLE TWO (2), MONTON CONTROL STATIONS, TP AND UNSTRABLE TWO (2), MONTON CONTROL STATIONS, TP AND UNSTRABLE TWO (2), MONTON CONTROL STATIONS, TP AND UNSTRABLE TWO (2) PIETE POLE MONTHING BRACKET WAXE TWO (2) PIETE POLE MONTHING BRACKET WAXE TWO (2) PIETE POLE MONTHING MONTON THE FLY ONE (1), 147 ROOF LADORE TWO MONTON ON THE FLY ONE (1), ARRIVAL LADORE NOUR MONTON THE CLASSIS CAB TWO (2) LADORE SIGNS





NOTE:

DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO CHANGE AS MAY BE FOUND NECESSARY DURING CON-STRUCTION.

MINOR DETAILS MAY NOT BE SHOWN.

CHASSIS:
STYLE—SPARTAN MFD 4 DOOR
WHEELBASE—200 1/2
WHEELBASE—200 1/2
WHEELBASE—200 1/2
REPORT ALLE—200 LB MERTOR W/TAG AXLE
TRANSMISSION—ALLSON HD—4050 PP
FUEL CAPACITY—50 U.S. GALLONS
ALTERNATOR: 200 AMP NIEHOOFF



DATE	APPROVAL SIGNATURES		REVISIONS	
	DEALER	R.B.	BID PRINT MAR. 31, 1997	
	FIRE CHIEF	K.D.	UPDATED BID PRINT MAR. 12, 1998	i sn
	SALES AD.	R.B.	APPROVAL PRINT NOV. 18, 1998	SCALE:
	PRODUCTION			SHEET :
	ENGINEERING			FILENAM

	SMEAL FIRE APPARATUS SNYDER, NE 68664	СО
<u>neal</u>		
	DRAWN BY: DATE: SO#-	