



KIT DÉMO EN VENTE

OUTILS DE DÉSINCARCÉRATION À BATTERIE



COMPREND 2 BATTERIES ET 1 CHARGEUR.

ER40

TECHNICAL SPECS	STANDARD	METRIC
EXTENDED LENGTH	41.00 IN	1,041.4 MM
CLOSED LENGTH	25.50 IN	647.7 MM
HEIGHT	10.75 IN	273 MM
WIDTH	8.10 IN	205.7 MM
WEIGHT		
NO BATTERY	40.6 LBS	18.4 KG
ONE BATTERY	43.0 LBS	19.5 KG
MAX. PUSH FORCE	32,980 LBS	145 KN
MAX. PULL FORCE	7,800 LBS	34.7 KN
POWER SOURCE	28 VOLT MILWAUKEE BATTERY	
NFPA 1936-2015 CERTIFIED	YES	
IP RATING	54	



COMPREND 4 BATTERIES ET 2 CHARGEURS.

ESL28D

TECHNICAL SPECS	STANDARD	METRIC
LENGTH	34.5 IN	876.3 MM
HEIGHT	8.9 IN	226 MM
WIDTH	13.6 IN	345.4 MM
WEIGHT		
NO BATTERIES	44.6 LBS	20.2 KG
ONE BATTERY	46.8 LBS	21.2 KG
TWO BATTERIES	49 LBS	22.2 KG
MAX. SPREAD DISTANCE	28.00 IN	711.2 MM
MAX. SPREAD FORCE RANGE	32,150 - 178,330 LBS	143 - 793 KN
MAX. PULL FORCE	26,800 LBS	119 KN
POWER SOURCE	28 VOLT MILWAUKEE BATTERY	
NFPA 1936-2015 CERTIFIED	YES	
IP RATING	54	



COMPREND 4 BATTERIES ET 2 CHARGEURS.

ESLC29D

TECHNICAL SPECS	STANDARD	METRIC
LENGTH	32.5 IN	825.5 MM
HEIGHT	9.5 IN	241.3 MM
WIDTH		
NO BATTERIES	10.5 IN	266.7 MM
ONE BATTERY	11.38 IN	289 MM
TWO BATTERIES	12.6 IN	320 MM
WEIGHT		
NO BATTERIES	49.4 LBS	22.4 KG
ONE BATTERY	51.6 LBS	23.4 KG
TWO BATTERIES	53.8 LBS	24.4 KG
MAX. BLADE OPENING	7.0 IN	177.8 MM
POWER SOURCE	28 VOLT MILWAUKEE BATTERY	
NFPA 1936-2015 CERTIFIED	YES	
NFPA CUT TEST	A8, B9, C9, D9, E9	
IP RATING	54	